

**I .Installation Notice**

1. Install water supply lines in accordance with this manual.
2. Install the faucet only after the completion of house interior decoration in case paint or other chemicals erode the faucet surface.
3. Clean pipes to get rid of mud, sand or other debris blocked in pipes.
4. Wrap the thread part with Teflon tape before it is screwed. (Check whether the threads can be matched. Otherwise, too strong force applied to the wrench will damage the faucet).
5. After installation, check all the joints to make sure they are firmly connected. Turn on and off repeatedly to ensure there is no leakage around the joints. At this stage, the product is ready for normal use.
6. Keep the manual to the user.

**II .Operation Notice**

1. The product is used between water pressure 0.05~1.0MPa, water temperature 0~90°C.
2. Do not hang heavy things on the faucet.
3. Regularly clean the surface of faucet in neutral wash solution. Then dry it with a piece of soft cotton cloth to keep it bright.
4. Do not disassemble the product unless you are an expert.

**■ Installing Steps**

1. Install the handshower inlet inside the wall at 1.3m height off the ground. Drill two Ø8 holes 600mm higher than the inlet and insert the anchors. Fix the mounting piece onto the wall with the self-tapping screw.
2. Wrap the adapter with the Teflon tape and screw it onto the handshower inlet, then screw the connecting rod on the adapter. Adjust the connecting rod to keep the thread part downward.
3. Fix one end of the slide rail set onto the mounting piece and fix them with setscrew. Slide the other end into the connecting rod, and fix them with M5 screw.
4. Connect the handshower with the shower hose.
5. Turn on water for inspection.

**■ Diagram**

