

Model: CONTOUR NATURAL(4P/C) 33,3X100(A)

Codes: 100295096 - V13895791

Water absorption: BIII - Revestimiento ( $10\% \leq E \leq 20\%$ )



## DIMENSIONAL FEATURES

UNE-EN ISO 10545-2

Length	1000 MM	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*
Thickness	12 MM	+/-5%*
Width	332.8 MM	

\*ISO-13006:2018 UNE-EN 14411:2016

## MECHANICAL FEATURES

UNE-EN ISO 10545-4-6-7-11

Abrasion resistance	No Aplica	
Breaking strength	1320 N	>600N*
Crazing resistance	Resists 3 cycles	
Modulus of rupture	26 N/MM2	>=12N/mm2*

\*ISO-13006:2018 UNE-EN 14411:2016

## HYGIENIC FEATURES

UNE-EN ISO 10545-13-14:1995

Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance	Class 5. Easy cleaning with water	3 Min.*

\*ISO-13006:2018 UNE-EN 14411:2016

## SCOPE OF USE

Technical code-1	Use on walls	
------------------	--------------	--

## ANTI-SLIP VALUE

UNE 41901:2017 EX, UNE 41902:2017 EX, DIN-51130 y ASTM C1028

Friction (dry)	No Aplica	
Friction (wet)	No Aplica	
Slip resistance (dcof)	No Aplica	

\*ISO-13006:2018 UNE-EN 14411:2016

System Certification



V13895791  
100295096

CONTOUR NATURAL

PACKING		
Boxes	1.332 M2/BOX	
Pallets	58.6081 M2/PAL	
Units	0.333 M2/PIECE	

System Certification

