

Model: CONTOUR BEIGE(4P/C) 33,3X100(A)

Codes: 100295011 - V13895721

Water absorption: BIII - Revestimiento (10%≤E≤20%)



**DIMENSIONAL FEATURES**  
UNE-EN ISO 10545-2

Length	1000 MM	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*
Thickness	12 MM	+/-5%*
Width	332.8 MM	

\*ISO-13006:2018 UNE-EN 14411:2016

**MECHANICAL FEATURES**  
UNE-EN ISO 10545-4-6-7-11

Abrasion resistance	No Aplica	
Breaking strength	1362 N	>600N*
Crazing resistance	Resists 3 cycles	
Modulus of rupture	27 N/MM2	>=12N/mm2*

\*ISO-13006:2018 UNE-EN 14411:2016

**HYGIENIC FEATURES**  
UNE-EN ISO 10545-13-14:1995

Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance	Class 5. Easy cleaning with water	3 Min.*

\*ISO-13006:2018 UNE-EN 14411:2016

**SCOPE OF USE**

Technical code-1	Use on walls	
------------------	--------------	--

**ANTI-SLIP VALUE**  
UNE 41901:2017 EX, UNE 41902:2017 EX, DIN-51130 y ASTM C1028

Friction (dry)	No Aplica	
Friction (wet)	No Aplica	
Slip resistance (dcof)	No Aplica	

\*ISO-13006:2018 UNE-EN 14411:2016

System Certification



V13895721  
100295011

CONTOUR BEIGE

**PORCELANOSA**  
PORCELANOSA Grupo

**PACKING**

Boxes	1.332 M2/BOX	
Pallets	58.6081 M2/PAL	
Units	0.333 M2/PIECE	

System Certification



Do not use cleaning agents containing hydrofluoric acid.  
It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.  
For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double glueing technique.  
Mosaic tiles must be grouted.  
This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.