

I .Installation Notice

1. Install water supply lines in accordance with this manual.
2. Install the faucet only after the completion of house interior decoration in case paint or other chemicals erode the faucet surface.
3. Clean pipes to get rid of mud, sand or other debris blocked in pipes.
4. Wrap the thread part with Teflon tape before it is screwed. (Check whether the threads can be matched. Otherwise, too strong force applied to the wrench will damage the faucet).
5. After installation, check all the joints to make sure they are firmly connected. Turn on and off repeatedly to ensure there is no leakage around the joints. At this stage, the product is ready for normal use.
6. Keep the manual to the user.

II .Operation Notice

1. The product is used between water pressure 0.05~1.0MPa, water temperature 0~90°C.
2. Do not hang heavy things on the faucet.
3. Regularly clean the surface of faucet in neutral wash solution. Then dry it with a piece of soft cotton cloth to keep it bright.
4. Do not disassemble the product unless you are an expert.

■ Installing Steps

1. Install the water pipe in the wall at the height of 1.2m off the ground.
2. Drill one Ø8 hole 700mm higher than water pipes, insert the anchor.
3. Fix the mounting piece on the wall with the self-tapping screw.
4. Separately put the two escutcheons onto the shower adapter and the connecting rod. Wrap the Teflon tap around the thread of inlet end and then connect with the water pipes.
5. Put the lower riser of the slide rail set into the positioning hole of the shower adapter. Slide the upper riser onto the mounting piece and tighten it with the M5 screw. Then put the two escutcheons.
6. Connect the handshower with the shower hose.
7. Turn on water for inspection.

■ Diagram

