

Model: ARTIC 45X120(A) Codes: 100244436 - V30800631 Water absorption: BIII - Revestimiento (10%<=E<=20%)





DIMENSIONAL FEATURES UNE-EN ISO 10545-2			
Length	1200 MM		
Length and width deviation	Below 0.15%	+/-0.3%*	
Side straightness deviation	Below 0.15%	+/-0.3%*	
Squareness deviation	Below 0.15%	+/-0.3%*	
Surface flatness deviation	Below 0.15%	+/-0.4%*	
Thickness	10 MM	+/-5%*	
Width	450 MM		
*ISO-13006:2018 UNE-EN 14411:2016			
		50	

UNE-EN ISO 10545-4-6-7-11				
Breaking strength	1507 N	>600N*		
Crazing resistance	Resists 3 cycles			
Modulus of rupture	26 N/MM2	>=12N/mm2*		
*ICO 42000 2040 UNE EN 44444 2040				

*ISO_13006.2018 LINE_EN 1//11.201	
	06:2018 UNE-EN 14411:2016

HYGIENIC FEATURES
LINE-EN ISO 10545-13-14-1995

(resists attack). Minimum Class "B" for acids and bases

B Min.*

3 Min.*

Class "A" for swimming pools and cleaning products

Class 5. Easy cleaning with water

Use on walls

No Aplica

resistance

Stain resistance

*ISO-13006:2018 UNE-EN 14411:2016

SCOPE OF USE

Technical code-1

ANTI-SLIP VALUE

UNE 41901:2017 EX, UNE 41902:2017 EX, DIN-51130 y ASTM C1028

Dynamic coefficient of friction

*ISO-13006:2018 UNE-EN 14411:2016

PACKING		
Boxes	1.62 M2/BOX	
Pallets	64.7983 M2/PAL	
Units	0.54 M2/PIECE	



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.